



ENERGY 2.5

# ENERGY 2.5 SERIES




## ENERGY 2.5 VINYL FLOORING



Sea Salt **VYESS748**



Silver Cloud **VYESC748**



Camel **VYECM748**



Oysterwood **VYEOW748**



Shark Skin **VYESK748**



Bluff **VYEBF748**



Fossil **VYEFS748**



Caramel **VYECR748**



Hyde **VYEHY748**



Lead **VYELD748**






### RETAIL PRICING LISTED

Stocked Sizes	Price /sf	Price / box
7.25" x 48"	\$3.95	\$171.83









For more info, visit:  
[www.amestile.com/energy25](http://www.amestile.com/energy25)

# ENERGY 2.5 SERIES













## Technical Data and Options

	Overall Thickness	0.098" (2,5 mm)
	Wear Layer Thickness	0.020" (0,50 mm)
	Plank Size	7.25" x 48" (18,4 cm x 122 cm)
	Packaging	18 planks/43.5 Sq.f./38.9 lbs (17.67 Kg)/Box
	Installation	Full Spread Adhesives




## Construction

	ASTM F1700, Class III, Type B	Section 5.5.1 Commercial Applications  
	100% Pure solid vinyl	100% Recyclable
	Printed design	Hi-Definition natural visual and embossing options
	Bevel edge profile	Four Sides
	Phthalate Safe	EN 14372 Compliant
	Anti-Bacterial	ASTM G21 No Growth Compliant
	Maintenance	UV-urethane antimicrobial, durable finish for a no wax easy maintenance

## Performance

	Abrasion resistance	ASTMD 4060	EN 660-2 Group T	Excellent
	Static Load Limit / Indentation	ASTM F970	1000 PSI	Exceeds 250 PSI
	Resistance Castor Chair	EN 425 : suitable for office chairs with castors		Pass
	Dimensional Stability	ASTM F2199	Excellent	Pass
	Chemical Resistance	ASTM F925	Excellent	Pass
	Resistance to Radiant Heat	EN 12524	0.25 W/mK, Max 77° F (25° C)	Suitable for heated floors
	Impact Insulation Class	ISO 717-2	6 dB	Meets
	Sound Transmission Class	NF S 31-074	Class B	Meets
	Slip Resistance	ASTM D2047	ADA Requirement	Exceeds
	Fire Test Data – Flame Spread	ASTM E648	0.45 watt/cm <sup>2</sup> or more	Class I
	Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Meets
	Fire Test Data – Canada	CAN/ULC S-102.2	CDN Building Code	Compliant

## Supplement and Environment

	Indoor Air Quality	FloorScore	Certification Guidelines	SCS-EC10.3 2014
	Certified Low Emitting Adhesives	SCAQMD	Rule #1168	Meets
	Plants Certifications	ISO 14001, ISO 9002, OHSAS 18001		Certified

## Limited Warranty

	15 year Commercial / Lifetime residential
---	---