











Norwegian IVNOR548

	RETAIL PRICING LISTED	
Stocked Sizes	Price /sf	Price /box
5"x 48"	\$4.95	\$ 98.31



Sugar IVSUG548



Canyon IVCAN548



Monterrey IVMON548





Technical Specifications

Construction	Hardwood design SPC planks with embossing and bevelled edges. PUR/UV PurKleenTM protected wear layer; supported by a composite AquaKore structure and acoustic cork backing.	
Style	Drop Lock CLIC Floating Acoustic Installation System.	
Standard	ASTM F3261	
Total Thickness	5.5mm	
Wear Layer	0.30 mm (12 mil)	
Sizes	5" x 48"	
Packaging: Pieces Box	12	
Coverage: Sq.ft. / Box	19.86	
Weight: Kg Box	15.87	
Surface Finish	PUR/UV PurKleenTM Protection : No Wax, No Spray Buff, for the life of the product	
Chemical and Stain Resistance	ASTM F925 : Compliant	
Abrasion Resistance	ASTM F510: Compliant	
Slip Resistance	ASTM D2047 / R9 : Compliant	
Static Load Resistance	ASTM F970 : Compliant	
Wheel Castor Resistance	EN 425 : Compliant	
Dimensional Stability	ASTM F2199: Compliant	
In-floor Heating	Suitable for hydronic heated floor systems, maximum ambiant room temperature 28°C (82°F)	
Impact Insulation Class	ASTM E989 : 73 IIC	
Sound Transmission Class	ASTM E413 : 67 STC	
Flame Spread & Smoke Development	CAN/ULC-\$102.2 / ASTM E648 Class 1 / ASTM E662 : Compliant	
Phthalate Free	EN 14372 : Compliant	
Indoor Air Quality, VOC Emission	FloorScore Certied	
Recycling	100% Recyclable	
Plant Certifications	ISO 9002, ISO 14001, OHSAS 18001	
Health & Safety	Complies with REACH regulations	
Limited Warranty	Residential: Lifetime	

