




# RELIANT 2.0 SERIES



## RELIANT 2.0 VINYL FLOORING



Debutante **VYRDB748**



Aspen **VYRAP748**



Coastal Path **VYRCH748**



Mason **VYRMS748**



Compass **VYRCP748**



Arbor **VYRAR748**








Bristol **VYRBR748**

### RETAIL PRICING LISTED








Stocked Sizes	Price /sf	Price /box
7.25" x 48"	\$2.95	\$156.85

# RELIANT 2.0 SERIES













## Technical Data and Options

	Overall Thickness	0.080" (2,0 mm)
	Wear Layer Thickness	0.012" (0,30 mm)
	Plank Size	7.25" x 48" (18,4 cm x 122 cm)
	Packaging	22 planks/53.17 Sq.f./42.4 lbs (19.27 Kg)/Box
	Installation	Full Spread Adhesives




## Construction

	ASTM F1700, Class III, Type B	Light Commercial 	
	100% Pure solid vinyl	100% Recyclable	
	Printed design	Hi-Definition natural visual and embossing options	
	Bevel edge profile	Four Sides	
	Phthalate Safe	EN 14372	Compliant
	Anti-Bacterial	ASTM G21 No Growth	Compliant
	Maintenance	UV-urethane antimicrobial, durable finish for a no wax easy maintenance	

## Performance

	Abrasion resistance	ASTM D4060	EN 660-2 Group T	Excellent
	Static Load Limit / Indentation	ASTM F970	1500 PSI	Exceeds 250 PSI
	Resistance Castor Chair	EN 425 : suitable for office chairs with castors		Pass
	Dimensional Stability	ASTM F2199	Excellent	Pass
	Chemical Resistance	ASTM F925	Excellent	Pass
	Resistance to Radiant Heat	EN 12524	0.25 W/mK, Max 77° F (25° C)	Suitable for heated floors
	Impact Insulation Class	ISO 717-2	5 dB	Meets
	Sound Transmission Class	NF S 31-074	Class B	Meets
	Slip Resistance	ASTM D2047	ADA Requirement	Exceeds
	Fire Test Data – Flame Spread	ASTM E648	0.45 watt/cm <sup>2</sup> or more	Class I
	Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Meets
	Fire Test Data – Canada	CAN/ULC S-102.2	CDN Building Code	Compliant

## Supplement and Environment

	Indoor Air Quality	FloorScore	Certification Guidelines	SCS-EC10.3 2014
	Certified Low Emitting Adhesives	SCAQMD	Rule #1168	Meets
	Plants Certifications	ISO 14001, ISO 9002, OHSAS 18001		Certified

## Limited Warranty

	10 year Light Commercial / Lifetime residential
--	---